


KONDOR 3

ARNÉS

FICHA TÉCNICA

Producto



Descripción






- Anclaje anticaídas dorsal.
- Anclaje anticaídas esternal con estructura de cintas en X.
- Anillas laterales de posicionamiento.
- Hebillas de ajuste manual de acero cincado de alta resistencia.
- Cintas regulables en altura y perneras.
- Dos portaganchos plásticos incorporados en la parte frontal.
- Fabricación bicolor, para una mejor diferenciación de la parte superior e inferior.
- Chip NFC Ready: Chip incorporado para trazabilidad de producto, estado y revisión.

CARACTERÍSTICAS

Características generales	Norma	ANSI Z359.11
	Talla	Universal
	Peso	1380g
	Capacidad de uso	140kg
	Ancho cinta	44mm
	Vida útil	10 años de uso + 2 años de almacenamiento


Materiales	Componente	Material
	Cinta	Poliéster
	Hilo	Poliamida
	Anillas	Acero
	Hebillas de ajuste manual	Acero cincado

USOS

Puntos de enganche						
	KONDOR 1	●	-	-	-	-
	KONDOR 2	●	●	●	-	-
	KONDOR 3	●	●	●	-	-

HARNESS

Product








Description

- Dorsal fall arrest anchorage.
- Sternal fall arrest anchorage with X-strap structure.
- Lateral positioning rings.
- High-strength zinc-plated steel manual adjustment buckles.
- Adjustable height and leg straps.
- Two plastic hook holders built into the front.
- Two-colour construction, for a better differentiation of the upper and lower part.
- NFC Ready Chip: Built-in chip for product traceability, status and revision.

CHARACTERISTICS

General characteristics	Norma	ANSI Z359.11
	Size	Universal
	Weight	1380g
	Capacity to use	140kg
	Tape width	44mm
	Shelf life	10 years of use + 2 years of storage
Materials	Component	Material
	Tape	Polyester
	Thread	Polyamide
	Rings	Steel
	Manually adjustable buckles	Galvanised steel

USES

Hitching points						
	KONDOR 1	●	-	-	-	-
	KONDOR 2	●	●	●	-	-
	KONDOR 3	●	●	●	-	-